

## VFI Coverage Chart

|                   | VFI Product #     | Product Description                       | 10 Year   | 15 Year   | 20 Year  |             |
|-------------------|-------------------|---|---|---|--|-------------|
| SILICONE COATINGS | <b>VFI-990</b>    | <b>High Solids Silicone- Solvent Free</b> |   |   |  |             |
|                   |                   | <b>Mod Bit (No Primer)</b>                | 2.0 gals/ square<br>50 sq ft/ gal<br>1 coat   | 2.5 gals/ square<br>40 sq ft/ gal<br>1 or 2 coats   | 3.0 gals/ square<br>33 sq ft/gal<br>2 or 3 coats     |             |
|                   |                   | All Other Surfaces                        | 1.5 gals/ square<br>66 sq. ft./ gal<br>1 coats  | 2.0 gals/ square<br>50 sq. ft./ gal<br>1 or 2 coats   | 2.5 gals/ square<br>40 sq. ft./ gal<br>2 or 3 coats  |             |
|                   | <b>VFI-991</b>    | <b>Low Solids Silicone- Solvent Based</b> |   |   |  |             |
|                   |                   | <b>Mod Bit (No Primer)</b>                | 2.75 gals/ square<br>36 sq. ft./ gal<br>1 or 2 coats  | 3.5 gals/ square<br>28 sq. ft./ gal<br>2 coats  | 4.25 gals/ square<br>23 sq. ft./ gal<br>2 or 3 coats |             |
|                   |                   | All Other Surfaces                        | 2.0 gals/ square<br>50 sq. ft./ gal<br>1 or 2 coats   | 2.7 gals/ square<br>37 sq. ft./ gal<br>2 coats  | 3.4 gals/ square<br>29 sq. ft./ gal<br>2 or 3 coats  |             |
|                   | <b>VFI-993</b>    | <b>Flashing Grade Silicone</b>            | 1 gal will treat approximately 150 lineal ft. of seams<br>1 gallon will treat approximately 450 fasteners |   |  |             |
|                   | <b>VFI-994</b>    | <b>Clear Silicone- Skylight Renewal</b>   | 1.5 gals/ square<br>66 sq. ft./ gal<br>2 coats  | 1.5 gals/ square<br>66 sq. ft./ gal<br>2 coats  | 1.5 gals/ square<br>66 sq. ft./ gal<br>2 coats       |             |
|                   | <b>VFI-990 SY</b> | <b>Silicone Walk Pad- Safety Yellow</b>   | <b>Low Traffic-</b> 2 gallons/ square<br>50 sq. ft./ gallon   |   |  |             |
|                   |                   |   | <b>High Traffic-</b> 2.75 gallons/ square<br>36 sq. ft./ gallon   |   |  |             |
|                   | ACRYLIC COATINGS  | <b>VFI-640</b>                            | <b>Acrylic Base Coat</b>  |   |  |             |
|                   |                   |   | <b>Mod Bit (No Primer)</b>  | 5.0 gals/ square<br>20 sq ft/ gal   | 5.0 gals/ square<br>20 sq ft/ gal                    | X<br>X      |
|                   |                   |   | <b>Mod Bit (Primer)</b>   | 3.3 gals/ square<br>30 sq ft/ gal   | 3.3 gals/ square<br>30 sq ft/ gal                    | X<br>X      |
|                   |                   |   | All Others Surfaces   | 2.7 gals/ square<br>37 sq ft/ gal   | 2.7 gals/ square<br>37 sq ft/ gal                    | X<br>X      |
|                   |                   | <b>VFI-605</b>                            | <b>Acrylic Top Coat (All Surfaces)</b>  | 1.5 gals/ square<br>66 sq. ft./ gal<br>1 or 2 coats   | 2.25 gals/ square<br>44 sq. ft./ gal<br>2 or 3 coats | X<br>X<br>X |
|                   |                   | <b>VFI-630</b>                            | <b>Acrylic Flashing Grade</b>   | 1 gal will treat approximately 150 lineal ft. of seams<br>1 gallon will treat approximately 450 fasteners |  |             |
|                   |                   | <b>VFI-680</b>                            | <b>Fluoropolymer Coating</b>  | 0.66 gallons/ square<br>150 sq ft/ gallon<br>2 coats  |  |             |

|   |  |  |  |                     |
|---|--|--|--|---------------------|
| ACRYLIC COATINGS  | <b>VFI-608</b>   | <b>Below Grade Application</b>           | 1.33 gallons/ square                   |                     |
|   | Mix:<br><br>1 part VFI-608<br>1 part water<br>3 parts portland cement Type I, II |  | 75 sq. ft./ gallon                     |                     |
|   |  |  | 3 coat application with fabric         |                     |
|   |  | <b>Deck Application Under Tile</b>       | 0.66 gallons/ square                   |                     |
|   |  |  | 150 sq. ft./ gallon                    |                     |
|   |  |  | 3 coat application with fabric         |                     |
| TRAFFIC COATING   | <b>VFI-3220</b>  | <b>3- Part Traffic Topping For Decks</b> | 300 sq. ft./ 5 gallon kit              |                     |
|   |  |  | 2 coat application                     |                     |
| Part A: Slack-Filled Five Gallon Pail<br><br>Part B: Catalyst- Pour Into Part A<br><br>Colorant: Pour into Part A<br><br>Mix All Parts Together Evenly To Make 5 Gallon Kit |  |  |  |                     |
| PRIMERS & CLEANER   | <b>VFI-607</b>   | <b>Granual Locking Primer</b>            | 0.8 gals/ square                       |                     |
|   |  |  | 120 sq ft/ gal                         |                     |
|   |  |  | 1 coat                                 |                     |
|   | <b>VFI-608</b>   | <b>Concrete Primer</b>                   | 0.33 gals/ square                      |                     |
|   |  |  | 300 sq ft/ gal                         |                     |
|   |  |  | 1 coat                                 |                     |
|   | <b>VFI-690</b>   | <b>Waterproofing Primer for Walls</b>    |  |                     |
|   |  | <b>Rough Surfaces</b>                    | 1 gallon/ square                       |                     |
|   |  |  | 100 sq ft/ gallon                      |                     |
|   |  |  | 1 or 2 coats                           |                     |
|   |  | <b>Smooth Surfaces</b>                   | 0.5 gallons/ square                    |                     |
|   |  |  | 200 sq ft/ gallon                      |                     |
|   |  |  | 1 coat                                 |                     |
|   |  | <b>VFI-11</b>                            | <b>2 Part Water Based Epoxy Primer</b> |                     |
|   |  |  | <b>Light Rust</b>                      | 0.5 gallons/ square |
|   |  |  |  | 200 sq. ft./ gallon |
|   |  |  |  | 1 coat              |
|   |  |  | <b>Heavy Rust</b>                      | 1.0 gallons/ square |
|   |  |  |  | 100 sq. ft./ gallon |
|   |  |  |  | 2 coats             |
|   |  | <b>Mod Bit</b>                           | 1.0 gallons/ square                    |                     |
|   |  |  | 100 sq. ft./ gallon                    |                     |
|   |  |  | 1 coat                                 |                     |
|   |  | <b>All Other Surfaces</b>                | 0.33 gallons/ square                   |                     |
|   |  |  | 300 sq. ft./ gallon                    |                     |
|   |  |  | 1 coat                                 |                     |

|                      |                    |                                      |   |                         |
|----------------------|--------------------|--------------------------------------|---|-------------------------|
| PRIMERS &<br>CLEANER | VFI-1007           | <b>Polyurethane Bonding Primer</b>   |   |                         |
|                      |                    | <b>Rough Or Pourous Surfaces</b>     | 1 gallon/ square<br>100 sq. ft./ gallon<br>1 coat     |                         |
|                      |                    | All Other Surfaces                   | 0.25 gallons/ square<br>400 sq. ft./ gallon<br>1 coat |                         |
|                      | VFI-1008           | <b>EPDM Wash Primer- Water Based</b> | 0.33 gallons/ square<br>300 sq. ft./ gallon<br>1 coat |                         |
|                      | VFI-1009           | <b>Cleaning Concentrate</b>          | Mix 1 part 1009 to 10 parts H2O                       |                         |
|                      |                    | <b>Normal Cleaning</b>               | 0.05 gallons/ square<br>2,000 sq. ft./ gallon         |                         |
|                      |                    | <b>Severe Cleaning</b>               | 0.1 gallon/ square<br>1,000 sq. ft./ gallon           |                         |
|                      | VFI-1074           | <b>Acrylic Rust Primer</b>           |   |                         |
|                      |                    | <b>Light Rust</b>                    | 0.5 gallons/ square<br>200 sq ft/ gallon<br>1 coat    |                         |
|                      |                    | <b>Severe Rust</b>                   | 1 gallon/ square<br>100 sq ft/ gallon<br>2 coats      |                         |
|                      | REINFORCING FABRIC | PF-04                                | <b>4" Fabric</b>                                      | 300 Lineal Ft. Per Roll |
|                      |                    | PF-06                                | <b>6" Fabric</b>                                      | 300 Lineal Ft. Per Roll |
|                      |                    | PF-12                                | <b>12" Fabric</b>                                     | 300 Lineal Ft. Per Roll |
|                      |                    | PF-20                                | <b>20" Fabric</b>                                     | 300 Lineal Ft. Per Roll |
|                      |                    | PF-40                                | <b>40" Fabric</b>                                     | 1,000 sq. ft.           |
|                      |                    | TA-04                                | <b>4" Fabric Backed Butyl Tape</b>                    | 50 Lineal Ft. Per Roll  |
|                      |                    | TA-06                                | <b>6" Fabric Backed Butyl Tape</b>                    | 50 Lineal Ft. Per Roll  |
|                      | TA-12              | <b>12" Fabric Backed Butyl Tape</b>  | 50 Lineal Ft. Per Roll                                |                         |