



VOLATILEFREE INC[®]
MANUFACTURERS OF HIGH PERFORMANCE POLYMERS

Sustainability
Durability
Flexibility

VFI[®]-600 Series Acrylic Restoration Coating System



Before VFI-600 Series



After VFI-600 Series

The VFI-600 Series includes VFI-605 (White Top Coat) and VFI-640 (Gray Base Coat). These combine and cure to form a seamless membrane. The system is formulated to achieve superior adhesion over metal, mod bit/BUR, single-ply, concrete, board-stock and sprayed-in-place polyurethane foam, and composite shingle roof substrates.

VFI-600 SERIES INCLUDES

- VFI-605 Premium Grade Elastomeric Top Coat
- VFI-640 Premium Grade Elastomeric Base Coat
- VFI-630 Flashing Grade Acrylic Coating

VFI-600 SERIES ADVANTAGES

- **Extends** the useful life of the roof
- **Offers** high tensile strength and elongation
- **Resistant** to dirt pick up
- **Offers** excellent resistance to emended exposure to solar ultraviolet energy
- By decreasing roof surface temperature, VFI-600 Series can **reduce energy costs**
- **Fungal and algal resistant**-even in high temperatures
- **Low VOC, non-flammable and presents minimal hazard** to the applicator or the environment



PRODUCT INFORMATION & APPLICATION

VFI-600 Series Acrylic Restoration System is a single component, water-based coating comprised of a top coat and base coat. The two part system can be sprayed, rolled or brushed onto the desired substrate.

VFI-605 Premium Grade Elastomeric Top Coat		VFI-640 Premium Grade Elastomeric Base Coat	
Color	white	Color	light gray or medium gray
Viscosity	28,000-58,000 cps	Viscosity	28,000-58,000 cps
Tensile Strength	350 +/- 50 psi	Tensile Strength	350 +/- 50 psi
Elongation	200 +/- 50 psi	Elongation	200 +/- 50 psi
Solids	Weight – 63% Volume – 51%	Solids	Weight – 63% Volume – 51%
Permeability	27 (wet), 13 (dry) perms	Permeability	27 (wet), 13 (dry) perms
Liquid Material Density & Specific Gravity	11 +/- .5	Liquid Material Density & Specific Gravity	11 +/- .5

Setting the standard for Renewable Coatings and Spray Foams

For more information, contact us today at **800-307-9218**

Check out our new website at www.volatilefree.com



This information and technical advice provided herein are believed to be reliable and accurate to the best knowledge of Volatile Free, Inc., As based on tests and should serve only as a recommendation. As the manufacturer, Volatile Free, Inc makes no representations or warranties of any kind, expressed, implied or statutory, including but not limited to all implied warranties of merchantability or fitness for use or a particular purpose, or any other matter with respect to this product. Volatile Free, Inc makes no representations or warranties as to the results of the use of the product and assumes no obligation or liability in connection therewith. Volatile Free, Inc is not liable for any special, exemplary, punitive, incidental or consequential damages of any sort or kind from use of this product. The information provided herein is subject to change at any time without notice. Information changes may include, but are not limited to, commercial and technical changes, changes in pricing, physical characteristics and packaging.